

राजेश शाह
मो. 94250-66839



श्री गिरिराज ट्रेडर्स

10/2-सी, महारानी रोड, इन्दौर- 452007

फोन : 0731-2434323, 4042704

Email : shrigirirajtradersindore@gmail.com

Authorised Dealer



Pumps & Motors
Crompton Greaves Ltd.



P.V.C. Industrial Hose
DUTRON PLASTICS LTD.



Jointing & Asb Products
CHAMPION SEALS
(INDIA) P. LTD



Dewatering
& Sewage Pumps
DARLING PUMPS PVT. LTD.



CONNECTING TECHNOLOGIES
PUMPS | MOTORS | PIPES | CABLES



KLIPCO®
HOSE CLAMPS



The name you can trust



"CF" SERIES SS CENTRIFUGAL PUMP

APPLICATION : RO Water, DM Water, Pure Water, Water for Injection (WFI), Alkaline Solution / Alcoholic Drinks, Acids, Fine Chemicals, Bottling Plants, Soft Drinks & Distillery, Food Processing / Liquid Food Stuffs, Descaling Applications Hot & Cold Water Pumping

HEAD : 04 Meters to 80 Meters

CAPACITY : 04 Lpm to 2000 Lpm

MATERIAL OF CONSTRUCTION : Casing/impeller (semi Open, Open) / Wear Plate/ Shaft : Aisi 316 / 316L / 304 / 304

MOTOR COVER : SS-304 / SS 202

GASKET : Viton / Nitrile / Silicon / PTFE



"CFS" SERIES SS CENTRIFUGAL PUMP

APPLICATION : Milk, Cream, Butter Milk, Condensed Milk, Fruit Juice, Beer, Wine, Sugar Syrup Vitamin Solutions, Sugar & Confectionery, Pharmaceutical Formulations, Paper & Cement Industries, Water Treatment Plants, Detergent, Soaps, Paste & Shampoo, Textile Sizing, Dyeing & Finishing Systems, Natural Cellulose Fiber / Synthetic Fiber System.

HEAD : 03 Meters to 76 Meters

CAPACITY : Up to 1890 Lpm

MATERIAL OF CONSTRUCTION : SS 304 / SS 316 / SS 304 L / SS 316 L



"BPO" SERIES BACK PULL OUT END SUCTION PUMP

APPLICATION : For pumping Clear / Chemicals & Volatile Liquids Air conditional Plants. Power station, Mine Drainage, Sprinkle systems firefighting, Booster service, Oils Brine

DELIVERY SIZE : Up to 250 mm

CAPACITY : Up to 990 m³/hr

HEAD : Up to 120 meters

RPM : 500 – 3600

MOTOR COVER : SS-304 / S 202

MATERIAL OF CONSTRUCTION : Cast Iron Construction with En-8 Shaft, SS-410 Sleeve, Gland Packing and special material like WCB, CF-8, CF-8M, Alloy 20, SS-304, SS-316 Fabricated etc on request



"AODD" SERIES AIR OPERATED DOUBLE DIAPHRAGM PUMP

APPLICATION : To Handle Viscous Chemicals, Slurries. To Transfer Explosive Liquids, Solvents, Acids. Pharmaceutical Liquids Creams And Compounds, Semi Solid Foods, Flavours, Drinks, Wine, Beer, Alcohols. Waste Water, Sewage Effluents, Coal And Lime Slurry. Hydrocarbons, Petrol Diesel, Lubrication Oil, Vegetable Oil. Paints Emulsions, Pigments, Thinners, Resins. Ceramics, Slip, Gases, Clays.

CAPACITY : 0-580 LPM

PRESSURE : Maximum 7 bar

MATERIAL OF CONSTRUCTION :- PP / SS / Aluminum / PVDF





MP" SERIES HORIZONTAL SELF PRIMING CUM CENTRIFUGAL NON CLOG PUMP

APPLICATION : Pumping Muddy Water, Sewage, Solid And In Swimming Pool , Flood Drainage , Dewatering Basements, Trenches, And Construction Sites, Effluent Plants, Transfer Of Clean Or Dirty Neutral, Acid Or Alkali Liquids Containing Sand, Mud Or Solids In Suspension; Clean Or Dirty Low Viscosity Petroleum Product Or Solvents; Milk Of Lime, Caustic Soda; Washing, Cooling, Circulation; Smoke Scrubbing; Emergency Duty. Cement Industries , Water Treatment Plants.

PRESSURE : UP TO 45 M

CAPACITY : UP TO 175 LPS

MATERIAL OF CONSTRUCTION : - CI / SS / BRONZE



GEAR PUMP

APPLICATION : Handling viscous and semi viscous liquid. Clean lube oil, Castor oil, Coconut oil, Ground nut oil, Cotton seed oil and Hydraulic oil. All kind of vegetable oils. Paints & Varnish, Viscous Chemical, Printing Ink. All Kind of fish and animal oils. Soap Solutions , Glycerin , Glycol and Glue Sugar molasses and syrups

PRESSURE : - UP TO 10 KG/CM2,

CAPACITY : 10 LPM – 500 LPM

MATERIAL OF CONSTRUCTION : CI / SS



SELF PRIMING PUMP

APPLICATION : All Clear Liquids Without Solid Suspensions Like Diesel, Petrol, Lpg, Oil, Solvents, Syrup, Dm Water, Chemicals, Steam Boiler Feeding, Evacuation Of Condensate Water, Boosting Of Pressure, As A Drum/barrel Pump., Firefighting – Mining , Wash Down Applications , Hydraulic Press/circuits Transfer & Circulation Hot & Cold Water

CAPACITY : 550 LPM

HEAD UP TO : 280 mlc Max

Suction Lift : 8 mlc Max

RPM : 500 – 3600

TEMPERATURE : 100°C Max

THESE PUMPS ARE SUITABLE ONLY FOR CLEAR LIQUIDS



PP CENTRIFUGAL PUMP

APPLICATION : Effluent Treatment , Filter Press For Dyes And Chemicals , Fertilizer Plants Thermal And Atomic Power Plants , Drugs & Pharmaceutical Industries , Descaling Of Tubes , Scrubbing Of Corrosive Gases Like C12 , Br , I So2 , Nh3 , F2 Etc. , Excellent For Vacuum Ejectors , Transferring Of Concentrated Hcl From Road Tankers , Paper & Pulp Industries , Pickling In Steel Rolling Mills , Caustic Soda Plants , Phosphoric Acid , Gas Washing Plants , Electro Plating,

CAPACITY : 180 m3/hr,

HEAD UP TO : 60 Mtrs

TEMPERATURE : Up to 110°C





“MMP” SERIES CENTRIFUGAL PUMP

APPLICATION : Irrigation, Industries for clear water handling Water supply for domestic use in apartments, Buildings and hotels.

HEAD UP TO : 90 meters

CAPACITY : Up to 40 liters per second

MATERIAL OF CONSTRUCTION : - Cast Iron Construction

OPTIONAL SUPPLY :

Impeller : Bronze / Stainless Steel

Shaft : Stainless steel

Shaft Sleeve : Chrome Steel



“RIL” SERIES VERTICAL INLINE CENTRIFUGAL PUMP

APPLICATION : Used generally for circulating clean nonaggressive fluids, Water Supply Systems, Water circulation / Transfer, Hot water Circulation, Agriculture, Industry, Ship Building, Cooling Towers, And many other Applications

HEAD : up to 95 mtr

CAPACITY : up to 280 m3/hr

HIGHER CAPACITY AND HEAD AVAILABLE ON REQUEST



“MPMD” SERIES SEAL LESS GLANDLESS MAGNETIC DRIVE CHEMICAL PROCESS PUMP PP & PVDF MATERIAL

Application : Ideal For Transfer Of Corrosive Chemicals, Acids, Dyes, Solvents, Toxic & Furning Liquids, Petrol, Kerosene Etc. Pharmaceuticals And Food Processing Electroplating, Galvanizing / Anodizing Plants. Laboratory Equipment's And Pcb Palnts. Medical Equipment's And X-ray Film Plants. Textile Dyeing Houses. Liquid Dispensing Machines For Hazardous Duty Conditions With Flame Proof Motors. High Efficiency Due To Permanent Magnet Power Coupling.

CAPACITY : from 10 LPM upto 750 LPM

HEAD : upto 40 mtrs

MATERIAL OF CONSTRUCTION : Poly Propylene Glass Filled, PVDF upto 110°C & SS-316

OPERATING TEMP : - PP upto 80°C, PVDF upto 110°C Special Pumps for high temperature upto 150°C and 250°C for SS-316

NOTE : All PMD Magnetic Drive Pumps are available in Monoblock type only with Std TEFC motor and Flame Proof motors.



HORIZONTAL (“CMS”) & VERTICAL (“VILM”) MULTISTAGE CENTRIFUGAL PUMP

APPLICATION : Water Treatment Plant, Hydro Pneumatic Systems / Condensate Transfer, Agriculture /Industrial Washing Coolant Circulation, Boiler Feeding / Fire Fighting / Booster Applications, Ship Building / Ro-dm Plants, Sprinkle Irrigation.

MAXIMUM HEAD :280 METER (vilm) / 400 m(cms)

MAXIMUM CAPACITY : 90 M3/HR (vilm) / 150 m3/hr(cms)





"LOBE" SERIES LOBE PUMP

Typical Applications for Positive Displacement Rotary Lobe Pumps:- Dairy , Bakery , , Meat Packing , Beverage ,Pharmaceutical , Canning , Confectionery , Cosmetics

OPERATING RANGE :

In Different Pressure Range up to 240 PSI And Flow Rate up to 750 LPM.



SEWAGE & DEWATERING SUBMERSIBLE PUMP

APPLICATION : U- Effluent with slurry and solids , Dewatering man-hole sewers. Storm/Flood water transfer , Drainage of sewage

HEAD : Up to 90 Mtr

CAPACITY : - Up to 3000 lpm (In High speed pump), Up To 15,000 lpm (In Low Speed pump)



SCREW PUMP

APPLICATION : Effluent Treatment, Chemicals , Dairy Fruits & Vegetable Processing Sweets & Confectioneries :- Paints & Waxes , Pulp & Paper Sugar & distilleries

DELIVERY SIZE : Up to 250 mm,

CAPACITY : - UP to 300 m³/hr HEAD :Up to 240 Mtr

MATERIAL OF CONSTRUCTION : Housing Parts Pump : Gray CI, Ss-304, Ss-316 & Special Alloys. Stator : Natural , Nitrile, Neoprene , Epdm , Hyplon , Viton , Food Grade & Special Quality Rubber. Rotor : Heat Treated Tool Steel , Ss-304 & Ss-316 And Other Special Alloys Rotating Parts : Tool Steel ,ss-304 , Ss-316 And Other Special Alloys



ELECTROMAGNETIC FLOW METER

APPLICATION : Water Supply Networks , Chemical, Petrochemical And Process Industries , Pharmaceutical Industries , Waste – Water Management , Sugar, Food , Drug And , Beverages Industries , Effluent Treatment Plants , Fertilizer Industries , Beverage Industries, Paper And Pulp Industries , Aluminium , Steel , Mining And Dredging Industries , And Many Others

SPECIFICATION:

Suitable For Pipe Sizes : Dn 10 To Dn 2000 Liner : Ptfе / Neoprene / Polyurethane

Media Conductivity (min) : 10 Ms/cm (consult Factory For 5 Ms/cm)

End Connection / Flanges: Carbon Steel / Ss 304 / Ss 316 / Ss 316l

Electrode : Ss/ Hastelloy C / Ta / Ti / Pt Coil Housing : Carbon Steel / Ss, Epoxy Painted

Power Supply : 110 / 240 V Ac + 15 % , 50 Hz / 24 V Dc

Analog Output : 4-20 Ma / Dc / 0-20 Ma Dc Flow Velocity Range : 0.3 To 10 M/s

Accuracy : 0.5 % Of Measured Value (calibrated) At Reference Conditions






Shri Giriraj Traders
श्री गिरिराज ट्रेडर्स

shrigirirajtradersindore@gmail.com

SPECIAL CUSTOMIZE PRODUCT PUMPS

			
AXIAL FLOW PUMP	VERTICAL TURBINE PUMP	LPG PUMP	VERTICAL SUMP PUMP
			
PULSATION DAMPER	BARREL PUMP	SHEAR PUMPS	NOZZLE & METER
			
FLOATING PUMPS	API PUMPS	VANE PUMPS	VERTICAL GLANDLESS PUMP
			
WATER METER	HYDRO TEST PUMP	FIRE PUMPS	SPECIAL MUD PUMP
			
VACUUM PUMP	PNEUMATIC PUMP	SOLAR DC PUMP	PISTON PUMP
			
DOSING & METERING PUMP	SPCF SERIES	PRIMING VALVE	HSC PUMP



अधिकृत वितरक/विक्रेता/स्टॉकिस्ट/ Authorised Distributor / Stockit / Dealer

Shri Giriraj Traders
श्री गिरिराज ट्रेडर्स

10/2-सी, महारानी रोड, इन्दौर- 452007

10/2-C, Maharani Road, Indore-452007 (MP) Phone : 0731-2434323 Fax : 0731-4042704

E-mail : shrigirirajtradersindore@gmail.com